

Reznor

Clean Burn

CABINET



Single-pass Blast tube design made of lighter weight 14 ga. stainless steel metal, does not allow for efficient heat exchange. Its poor design includes welding along the side of the tube which opens it up to potential heat stress damage.



Target at the rear of furnace is not easily accessed for cleaning and maintenance.



The combustion chamber is made of heavier, thicker 12 ga. carbon steel resulting in extra durability and more efficient heat exchange. On average, our furnaces weigh up to 175 lbs. more than many competitive furnaces.



Clean Burn furnace use several innovative multi-pass heat exchanger methods, depending on the size of the model, to ring out every last BTU of heat for your shop, while venting substantially cooler gases through the chimney than its competitors.

A Clean Burn Heat Exchanger provides approximately 200% more surface area for capturing combustion heat. You get more heat from less oil.



As it's furnace target Clean Burn uses an Energy Retention Plate made of innovative heat resistant material. It retains heat for

better heat transfer, protects the furnace, and is easily replaced. This view is looking down the heat exchanger with the Energy Retention Plate removed and in the foreground. Arrows point out easy attachment points.

BURNER



Modified Becket #2 oil burner converted for waste oil which makes for increased maintenance.



The Clean Burn burner is engineered from the ground up exclusively to burn used oils, and burns standard fuel oil for added versatility. A high quality on-board air compressor is optional, however most customers prefer to use their shop air.



Air compressor included -- considered noisy by some and a potential maintenance issue.



The pre-heater block heats oil and air to the same precise temperature for efficient combustion. Like its heat exchanger, it too uses a multi-pass heating approach.



Swing-away burner design provides quick, easy access to the combustion chamber. No need to disconnect oil, air and electrical lines. This unique modular design makes service faster and easier.

OIL PUMP



Light duty motor with nylon gears (grease)
Oil must be 50 degrees or greater, which limits the flexibility of an outdoor tank.

All models use a metering pump – 15' vertical rise and no more than 60' of total run (vertical rise is subtracted from max run) (light weight motor).

Additional covering needed due to unshielded motor and fan



The Clean Burn Pump features heavy-duty steel gears encased in an oil bath, and precision assembly to help ensure a long reliable service life. The oil flow rate is consistent because precise gear ratios and pump speeds are set for each individual furnace. A correct flow rate is maintained no matter what type of oil and viscosity is used, insuring optimum performance.



This brawny, reliable Clean Burn oil pump allows the furnace to be installed up to 300 ft. from the oil storage tank. It also permits the use of an outside storage tank where, in colder temperatures, many competitive pumps can't function. No competing waste oil furnace can provide such flexibility and convenience, from the initial installation to its day-to-day use.

SERVICEABILITY



Swing-out cabinet door.



Clean Burn's swing-out cabinet door makes cleaning and service easy.

SERVICE

Local service may be available. Contact your local sales representative for details.

Clean Burn has the largest service and distributor network in the industry, providing dependable installation and after-sale service and parts support.

Sandri Clean Burn

78 Main Street

Northfield, MA 01360

Toll Free: 1-800-882-4511 Ext 194 or 188

E-mail: cleanburn@sandri.com